



STEADY LINK™

# DATA SHEET

## SERIES-C

### 3/8 IN. RF50 CORRUGATED COAXIAL CABLE ASSEMBLY FLEXIBLE LOW PIM ASSEMBLY WITH STRAIGHT CONNECTORS



These Flexible Series-C Low PIM Coax Cable Assemblies have been designed to provide durable and reliable connections for transmitters, receivers, antennas and other applications in antenna feeder systems on cell towers. Features include low VSWR and strong shielding effectiveness to reduce energy loss and provide protection from outside interference. Part of NAI's STEADY LINK™ line, these assemblies are well suited for connections in low loss and VSWR signal transmission at high frequency applications.

Flexible Series-C Low PIM Coax Assemblies are made to order from inventoried materials with quick turn programs available.



### NAI COAX ASSEMBLY CONFIGURATOR

NAI's easy-to-use online configurator will walk you through a set of decisions to be made in order to provide you a quote or place an order for your coax assemblies.

[www.nai-group.com/configcoax](http://www.nai-group.com/configcoax)

## PRODUCT SPECIFICATIONS

### GENERAL DESCRIPTION

Impedance:	50 ohm
Lengths Available:	As Specified by Customer
Frequencies Available:	10 MHz to 3,000+ MHz
Peak Power:	13.2kW

### CABLE SPECIFICATIONS

Center Conductor:	Copper-plated Aluminum
Dielectric:	Foam PE
Outer Shield:	Helical Corrugated Copper
Jacket:	Black PE
O.D.	.425"

### CONNECTOR SPECIFICATIONS

Connector Types Available:

7-16 DIN (M)

4.3-10 (M)

4.1-9.5 (M)



<b>Connector Body:</b>	Brass, with Tri-metal plate
<b>Outer Contact:</b>	
Male:	Brass, with Tri-metal plate or Silver plate
<b>Center Contact:</b>	
Male:	Phosphorus Bronze, with Silver plate
<b>Dielectric:</b>	PTFE
<b>Sealing Material:</b>	Silicone Rubber
<b>Exterior Plastics:</b>	Zero Halogen, IEC 60754-1/-2
<b>Standards:</b>	RoHS Compliant



STEADY LINK™

## DATA SHEET

### PRODUCT SPECIFICATIONS (Continued)

#### ELECTRICAL SPECIFICATIONS

---

<b>Impedance:</b>	50 ohm +/-2 ohms
<b>PIM:</b>	2x20W, dBc ≤-160
<b>Standard:</b>	IEC 61196-1
<b>Return Loss (VSWR):</b>	Swept 690MHz-2700MHz [1.13-1.15]

#### MECHANICAL SPECIFICATIONS

---

<b>Bend Radius:</b>	25mm Single
<b>Tensile:</b>	950N
<b>Crush Resistance:</b>	2.0 kg/mm
<b>Sealing:</b>	IP 68
<b>Operating Temperatures:</b>	-55°C to ~+80°C
<b>Rel. Humidity:</b>	-40°C +/- 2°C, 90~95% @ 48 hours
<b>Storage Temperature:</b>	-55°C to ~+80°C

#### OTHER STEADY LINK™ ASSEMBLIES AND OPTIONS FROM NAI

---

NAI Series-C 50-Ohm Coax Cable Assemblies and Series-S GPS & Sync Cable Assemblies offer a variety of standard assembly configurations. Refer to the respective data sheet for each type.

- Series-C Low PIM 50-Ohm Corrugated Coax Assemblies with Straight-to-Straight Connectors
- Series-C Low PIM 50-Ohm Corrugated Flexible Coax Assemblies with Straight-to-Straight Connectors
- Series-C LMR\* 400 Coax Assemblies
- Series-C LMR\* 240 Coax Assemblies
- Series-S GPS and Sync Cable Assemblies
- Series-C Low PIM 50-Ohm Corrugated Flexible Coax Assemblies with Next10\*\* Connectors
- Series-C Low PIM 50-Ohm Corrugated Flexible and Regular Assemblies with Right Angle to Right Angle Connectors

\*Trademark of Times Microwave Systems, Inc.

\*\* Nex10 is a registered trademark of the Huber+Suhner, Radiall and Rosenberger consortium.